

ROAM XL

Add professional, license-free remote control to projects of any size with this long-range remote.

KEY BENEFITS

- Compatibility with Hunter X-Core®, X2™, Pro-C®, HPC, ICC2, HCC, I-Core®, ACC, and ACC2 controllers provides remote operation for a wide variety of landscapes
- Manually start individual stations or programs for quick maintenance checks and troubleshooting
- 128 programmable addresses available prevents cross-communication between multiple remotes within close proximity of each other
- Programmable run times from 1 to 90 minutes, which will not overwrite regular automatic programming
- Manual operation up to 240 stations provides flexibility for larger projects
- Rugged and water-resistant transmitter includes a large LCD display with simple push-button operation and a battery-life indicator

OPERATING SPECIFICATIONS

- Range: 2 miles (line of sight) from transmitter to receiver
- Transmitter power source: 4 x AAA batteries included
- Receiver power source: 24 VAC, 0.010 A
- System operating frequency: 27 MHz
- SmartPort® installation: maximum 50' from controller
- FCC approved (not available in EU and some other countries, check local regulations)
- Warranty period: 3 years



ROAM XL
(without antenna)
Height: 6¼"
Width: 3"
Depth: 1¼"



SmartPort
Hunter remotes require the installation of a SmartPort wiring harness. The SmartPort is a connector that is wired to the terminals on the controller, and allows quick connection to any Hunter receiver.



Wall-Mount Bracket for SmartPort
P/N 258200

ROAM XL

Model	Description
ROAMXL-KIT	Transmitter, receiver, SmartPort wiring harness, 4 AAA batteries and plastic carrying case included
ROAMXL-TR	Handheld transmitter and 4 AAA batteries included
ROAMXL-R	Receiver unit (SmartPort wiring harness included)

OPTIONS (SPECIFY SEPARATELY)

Model	Description
258200	Wall-mount bracket for SmartPort
ROAMXL-CASE	Plastic carrying case
ROAM-WH	SmartPort wiring harness (length: 6')
ROAM-SCWH	Shielded SmartPort wiring harness (length: 25')