



- 01 **Long Range:** Manually operate Hunter controllers up to 3.2 km away
- 02 **Rugged:** Heavy-duty, water-resistant shell built for the most demanding job sites
- 03 **Save Time:** Monitor system performance without unnecessary trips to and from the controller

ROAM XL LONG-DISTANCE REMOTE

Durable, Long-Range Remote Built for Contractors

Large-scale sites such as shopping centres, industrial properties, college campuses, and multi-unit housing complexes require high-powered remotes that can cover long distances. Hunter's ROAM XL remote is a powerhouse in a small package — but don't let its size fool you. While it's small enough to fit in your pocket, it boasts an open-field range of up to 3.2 km. It features a large LCD display, simple push-button operation, and 128 different programmable addresses. This compact yet high-powered remote can easily pair with any Hunter controller equipped with SmartPort® connectivity. With available run times up to 90 minutes, the ROAM XL eliminates the need to walk back and forth from the controller during system maintenance, repair, or winterisation.

Remote control is a must-have for any irrigation professional. Immediately save time and money with the flexibility and increased efficiency of Hunter's ROAM XL.

ROAM XL FEATURES & SPECIFICATIONS

Features & Specifications

- Up to 3.2 km range for remote manual operation of Hunter irrigation systems
- Compatible with Hunter X-Core®, Pro-C®/PCC, HPC, ICC2, HCC, I-Core®, ACC, and ACC2 controllers via SmartPort connection
- 128 different programmable addresses
- Maximum stations supported: 240
- Programmable run times: 1 to 90 minutes
- Large LCD display, push-button operation
- Run manual watering cycles without modifying regular program
- Transmitter power source: 4 AAA batteries (included)
- Receiver power source: 24 VAC, 10 mA (provided by controller)
- System operating frequency: 27 MHz band
- FCC approved, no licence required
- SmartPort connector can be mounted up to 7 m (max) from controller (using two ROAM-SCWH shielded cable wiring harnesses)
- Rugged plastic carrying case included
- Warranty: 3 years

Model

Long-distance remote for commercial and residential applications

ROAM XL

(w/o antenna)
 Height: 15.9 cm
 Width: 7.6 cm
 Depth: 3.2 cm



ROAM XL

Model	Description
ROAMXL-KIT	Transmitter, receiver, SmartPort® wiring harness, 4 AAA batteries, and carrying case
ROAMXL-TR	Handheld transmitter (4 AAA batteries included)
ROAMXL-R	Receiver unit (SmartPort wiring harness included)
ROAM-WH	SmartPort wiring harness (length: 1.8 m)
ROAM-SCWH	Shielded SmartPort wiring harness (length: 7.6 m)

Specifying Options

Hunter remotes require the installation of a SmartPort wiring harness*.



SMARTPORT

The SmartPort connector is wired to the AC1, AC2, and REM terminals on the controller, and allows quick connection to any Hunter remote.

* ACC, ACC2, I-Core, and ICC2 controllers include pre-wired SmartPorts for remote operation.



WALL-MOUNT BRACKET FOR SMARTPORT

P/N 258200

Website hunterindustries.com | Technical Service +1 760-591-7383

Helping our customers succeed is what drives us. While our passion for innovation and engineering is built into everything we do, it is our commitment to exceptional support that we hope will keep you in the Hunter family of customers for years to come.


 Gregory R. Hunter, CEO of Hunter Industries

